

FORMAT FOR PRICE - BID

Sl.No	Description	Qty	Unit	HSN CODE	Basic Unit Price /No	GST on basic unit price		P&F chgs. (if any per Unit)in %	P&F chgs. Amount in Rs. Per Unit	GST on P&F		Freight charges per Unit (if any)	GST on freight		Other Charges, if any per unit (Rs.)	GST on other charges		Total landed Cost Per unit in (Rs.) /No	
					(in Rs.)	(in %)	(in Rs.)		(In Rs.)	(in %)	(in Rs.)		(in %)	(in Rs.)	(in Rs.)	(in %)	(in Rs.)	(in fig)	(in words)
1	3phase squirrel cage induction motor, mounting:Flange, frame size: 132S-06, IP55, 415V, Connection-Y, 50Hz, 3.0kw, 965RPM, 6.83A, Make: WEG/ Equivalent in ABB/ CG/ Siemens/ Kirloskar/ Bharat Bijlee/ Marathon/ HML/ Nord/ PBL Application: Lube oil pumping purpose.	1	No																
2	3phase squirrel cage induction motor, mounting:Flange, frame size: AL90S/L-02, IP55, 415V, Connection-Y, 50Hz, 2.2kw, 2820RPM, 4.58A, Make: WEG/ Equivalent in ABB/ CG/ Siemens/ Kirloskar/ Bharat Bijlee/ Marathon/ HML/ Nord/ PBL Application: Hydro set pump unit lub oil cicalution.	1	No																
3	3phase squirrel cage induction motor, mounting:Flange, frame size: AL112M-4, IP55, 415V, Connection-Y, 50Hz, 4.0kw, 1445RPM, 8.18A, Make: WEG/ Equivalent in ABB/ CG/ Siemens/ Kirloskar/ Bharat Bijlee/ Marathon/ HML/ Nord/ PBL Application: Lube system cooling fan purpose.	1	No																
4	3phase squirrel cage induction motor, mounting:Flange, frame size: AL71-06, IP55, 415V, Connection-Y, 50Hz, 025kw, 905RPM, 6.83A, Make: WEG/ Equivalent in ABB/ CG/ Siemens/ Kirloskar/ Bharat Bijlee/ Marathon/ HML/ Nord/ PBL Application: pinion shaft motor.	1	No																
5	3phase squirrel cage induction motor, mounting:Flange, frame size: AL71-2, IP55, 415V, Connection-Y, 50Hz, 0.37kw, 2790RPM, 0.910A, Make: WEG/ Equivalent in ABB/ CG/ Siemens/ Kirloskar/ Bharat Bijlee/ Marathon/ HML/ Nord/ PBL Application: Over pressure fan.	1	No																

Note: Bidders should quote their Basic price/ Unit only in the above given format. Offers received for another unit shall not be considered and will be rejected.