

**Sub: Pulleys of Vacuum pumps in Neutral (4P-1A/D), Leach (6P-1A/H), & Motor**

Sl. No.	Material code	Material Description	Unit code	Stock in hand	Dues	Consumption rate	Item cat	Quantity required
1	(New) 300 021 021 462	V-Groove Pulley SPC 1200 X 10G along with machined Taper lock bush TLB 7060 TB 175 (for Leach & Neutral filter Vacuum pump)	01					02
2	(New) 300 021 021 463	V-Groove Pulley SPC 355 X 10G along with machined Taper lock bush TLB 4545 TB 108 (for Leach filter Vacuum pump Motor)	01					10
3	(New) 300 021 021 464	V-Groove Pulley SPC 385 X 10G along with machined Taper lock bush TLB 5050 TB108 (for Leach filter Vacuum pump Motor)	01					04
<p>Special Instructions, if any: -  <b>Make : KAKATI only</b></p> <p>Please note that :</p> <ol style="list-style-type: none"> <li>1. Pulley must be machined suitable to respective given taper lock bush.</li> <li>2. Tapper lock bush must machined to the given shaft size</li> </ol>								

Note - overall L<sub>1</sub> will be considered as L<sub>1</sub>

*Nick*  
*20/10/20*