

Supply of Manual operated ON/OFF Gate valve (For tanks and pump suction & Discharge) with the following specifications for  
**SDU RE DISSOLUTION SCHEME.**

Sl. No.	Material code	Material Description & Size	Unit code	Stock in hand	Dues	Consumption rate	Item cat	Quantity required
	(New) 400 074 091969	Valve Type: Gate valve with stellite overlay on seat and wedge. Size: 2", Rating: #150 Body & Bonnet: CF8M, Seating ring: CF8M Stl M.O.C: CF 8M (SS 316) Standard: API - 6D, Testing: API - 598 Stem: SS 316, Wedge: CF8M Stl Gaskets: SPW SS 304 Operation : Manual with hand wheel Working Temperature: 100 degree C Working fluid: Uranium Strong liquor Ph: Alkaline (12-14) Fasteners: A 193 R.B7 / A 194 GR.2H End connections: Flanges ANSI B16.5, dimension Standard.	01					10 nos (New)
2	(New) 400 074 091970	-do- Size: 4"	01					10 (New)
3	(New) 400 074 091971	-do- Size: 6"	01					4 (New)
4	(New) 400 074 091972	do- Size: 8"	01					2 (New)

Make: Micro finish / KSB/L&T/Weir BDK/Khimji - only

Note: Overall L1 for all items will be considered as L1 for evaluation (as a turnkey).

*[Signature]*