



PROPERTIES OF RUBBER	
1. HARDNESS:	40-55°A
2. T.S.(KG./SQ. CM)	180
3. %ELONG.	450-550
4. REBOUND RESILIENCE	55%
5. SP.GR.	1.1
6. ASH CONTENT	11%

PROPERTIES OF RUBBER	
1. HARDNESS:	40-55°A
2. T.S.(KG./SQ. CM)	180
3. %ELONG.	450-550
4. REBOUND RESILIENCE	55%
5. SP.GR.	1.1
6. ASH CONTENT	11%

PROPERTIES OF RUBBER	
1. HARDNESS:	40-55°A
2. T.S.(KG./SQ. CM)	180
3. %ELONG.	450-550
4. REBOUND RESILIENCE	55%
5. SP.GR.	1.1
6. ASH CONTENT	11%

PROPERTIES OF RUBBER	
1. HARDNESS:	40-55°A
2. T.S.(KG./SQ. CM)	180
3. %ELONG.	450-550
4. REBOUND RESILIENCE	55%
5. SP.GR.	1.1
6. ASH CONTENT	11%

PROPERTIES OF RUBBER	
1. HARDNESS:	40-55°A
2. T.S.(KG./SQ. CM)	180
3. %ELONG.	450-550
4. REBOUND RESILIENCE	55%
5. SP.GR.	1.1
6. ASH CONTENT	11%

PROPERTIES OF RUBBER	
1. HARDNESS:	40-55°A
2. T.S.(KG./SQ. CM)	180
3. %ELONG.	450-550
4. REBOUND RESILIENCE	55%
5. SP.GR.	1.1
6. ASH CONTENT	11%

PLAN  
FINISHED IMPELLER, WEIGHT 8.3 K.G.

PLAN  
FINISHED IMPELLER, WEIGHT 8.3 K.G.

COMPOSITION OF MATERIAL

**NOTES**

1. ~~GOLF RUBBER SHORE 1-40~~
2. THE IMPELLERS ARE PRESSURE MOULDED ON STEEL MS

1. ~~GOLF RUBBER SHORE 1-40~~
2. THE IMPELLERS ARE PRESSURE MOULDED ON STEEL MS

**URANIUM CORPORATION OF INDIA LTD.**  
(A GOVT. OF INDIA, DEPARTMENT OF ATOMIC ENERGY ENTERPRISE)  
JALGAON

**URANIUM CORPORATION OF INDIA LTD.**  
(A GOVT. OF INDIA, DEPARTMENT OF ATOMIC ENERGY ENTERPRISE)  
JALGAON

DENVER SRL 5\*5 IMPELLER

**SCALE: FULL SIZE**

APPROVED	DATE	DRG. NO. UCI/M-98/001

APPROVED	DATE	DRG. NO. UCI/M-98/001

APPROVED	DATE	DRG. NO. UCI/M-98/001