

**Sub: Requirement for Pulleys of Nuetral Filter Feed (4P-3 A/D) & Repulper Pumps (4P-7 A/D) and Motors**

Sl. No.	Material code	Material Description	Unit code	Stock in hand	Dues	Consumption rate	Item cat	Quantity required
1	300 021 021642	V-Groove Pulley SPB 280 X5G along with machined Taper lock bush TLB 3535TB 65 (for Neutral Filter Feed pump Motor)	01					08
2	300 021 021 046	V- Groove pulley SPB 170X 5G along with machined taper lock bush TLB 3020 TB 65 (for Neutral Filter Feed pump & for Neutral Repulper pump)	01					16
3	300 021 021047	V-Groove Pulley SPB 236 X5G along with machined Taper lock bush TLB 3535TB 65 (for Neutral Repulper pump Motor)	01					08
<p>Special Instructions, If anv: -  <b>Make : FENNER/ALASKA/SKF/EDGON/ESCON</b></p> <p>Please note that :</p> <ol style="list-style-type: none"> <li>1. Pulley must be machined suitable to respective given taper lock bush.</li> <li>2. Tapper lock bush must machined to the given shaft size</li> </ol>								

Note: overall L<sub>1</sub> will be Considered as L<sub>1</sub>

NO Lapun  
 20/10/12