

Specification for MCB

Sl.No.	Material code	Material Description		Unit code	Stock in hand	Dues	Consumption rate	Item Cat.	Quantity required
		No. of Poles	Single Pole						
		Rated Voltage	240 V AC						
		Rated frequency	50 Hz						
		Rated Insulation Voltage	690 V						
		Rated Impulse Voltage	4 kv						
		Operating Temperature	10 to 55 deg C						
		Humidity	95 % RH						
		Protection Class	IP 20						
		Mounting	clip on Din Rail						
		Installation Postion	Vertical / Horizontal						
		Case & Cover	Moulded , Flame retardant theroplastic material						
		Rated Current							
1	800:014:310:055	1 Amp							30
2	800:014:310:056	2 Amp							30
3	800:014:310:505	6 Amp							20
4	800:014:310:508	10 Amp							20
		No. of Poles	Double Pole						
		Rated Voltage	240 V AC						
		Rated frequency	50 Hz						
		Rated Insulation Voltage	690 V						
		Rated Impulse Voltage	4 kv						
		Operating Temperature	10 to 55 deg C						
		Humidity	95 % RH						
		Protection Class	IP 20						
		Mounting	clip on Din Rail						
		Installation Postion	Vertical / Horizontal						
		Case & Cover	Moulded , Flame retardant theroplastic material						
		Rated Current							
5	800:014:310:042	20 Amp							15
6	800:014:310:043	32 Amp							10

Make: Havells,L&T,Legrand,Anchor,Siemens