

1. Description of Item: Make **HONEYWELL**, Qty: **02 Nos**

New
400 070 005 588

Universal Switch Stick: 4216 3.00 (31.7 x 6)meters Universal Fiberglass Switch Stick constructed of closed cell foam-filled tubular fiberglass in accordance with ASTM Standard F711. The Hook operating rod, made of solid 3/8" (9.5mm) diameter fiber glass, is mounted on the exterior of the tool so that it can be easily wiped down prior to use.

The sticks have a standard splined head of 1.25" diameter. Length: 20 feet (6 Meters); Dia: 1.5; Tough thermoplastic head ferrule EZ Grip plastic hand Grip; Wide Opening 15/16" (28.8mm); Stainless steel hook Heavy rubber end cap.; All fiberglass used is tested at 50kV / 6 inches (100kV / foot) and meets the dielectric leakage requirements of ASTM F711.
9840 splined Universal Head We can supply you tools as per your requirement (Switch Stick shall be constructed of closed cell foam-filled tubular fiberglass in accordance with ASTM F711. Hook operating rod made of solid 3/8" (9.5mm) diameter fiber glass, is mounted on the exterior)

2. Description of Item: Make **HONEYWELL**, Qty: **03 Nos**

New
400 070 005 587

22629:STATIC DISCHARGE STICK

Salisbury By Honeywell: 22629 The Static Discharge Stick is Designed to safely remove the static charge after de-energizing. This tool is pre-assembled and includes a brass alloy "U" hook, closed cell foam-filled tubular fiberglass switch stick made in accordance with ASTM Standard F711. Static discharge sticks have 6 feet of copper grounding cable attached to a Salisbury 1814 flat jaw, grade 3, bronze serrated clamp with strain relief along with Universal Switch Stick 4214 UNIV SWITCH STICK 1.25" X 4' Total Length : 0.3 meter earth rod and 1.2 Meter Universal Switch Stick

3. Description of Item: Make **HONEYWELL**, Qty: **02 Nos**

New
400 070 005 586

24401: RESCUE HOOK

Insulated Rescue Hook is an invaluable tool for any workplace. It's used to withdraw an injured worker out of a hazardous area. Confined spaces, in vaults, or just near electrical cabinets and switch gear are some of the places where this tool is a must. Featuring foam filled, fiberglass reinforced handle for superior electrical insulation and a coated heat treated body hook with an 18" opening. The stick is available in the standard lengths of 6 and 8 feet.
ASTM

Mhed
24/12/16