

URANIUM CORPORATION OF INDIA LIMITED

P.O.M.C.PALLI, DR.YSR DT, ANDHRAPRADESH-516349.

PHONE NO.08588-294404, E-MAIL-tmplpur@uraniumcorp.in

CORRIGENDUM-2

GeMTender Number:GeM/2026/B/8035069 Date:14/09/2026 for Transporter Belt Technical Specifications of Annexure-B for Lause B (2)(Page Number.03) &Wear belt technical Specifications (Page Number.06) is amended is given below.

1. **For:** Endless, drainage belt to be procured from M/s Dongil rubber belt co.ltd – South Korea/BELT TS – ITALY/ CONTITEC - GERMANY. The transporter belt shall have a minimum thickness of **38mm** and shall be made of SBR with hardness of 60 $\pm$ 5 $^{\circ}$ ShoreA & shall have polyester carcass. The main transporter belt shall have facility to reduce friction while moving on the Air boxes, Natural rubber lined belt support rollers / supports etc. Supply of two numbers (02nos.) endless drainage belts identical to existing for Horizontal belt filter (HBF) system –for Leach slurry filtration, each having filtration area of 110 m²having specifications as below:
2. **Read :** Endless, drainage belt to be procured from M/s Dongil rubber belt co.ltd – South Korea/BELT TS – ITALY/ CONTITEC - GERMANY. The transporter belt shall have a minimum thickness of **33mm** and shall be made of SBR with hardness of 60 $\pm$ 5 $^{\circ}$ ShoreA & shall have polyester carcass. The main transporter belt shall have facility to reduce friction while moving on the Air boxes, Natural rubber lined belt support rollers / supports etc. Supply of two numbers (02nos.) endless drainage belts identical to existing for Horizontal belt filter (HBF) system –for Leach slurry filtration, each having filtration area of 110 m²having specifications as below:
3. **For**

SPECIFICATIONFORHBFWEARBELT	
Duty	To work as vacuum seal belt for horizontal belt filter under 600mm Hg vacuum. Top surface will be sealing surface and bottom surface will slide on UHMWPE slide blocks. Plain water will be lubricant.
Equipment	Horizontal belt filter size 4.2mtr x 110m ²
MOC	PP–Polypropaline
Type of belt	Endless
Total wear Belt length	56850mm
Belt Width	50mm
Total Belt thickness	6mm (+0.00,-0.5mm)
No. Of Ply	3(cotton carcass)
Top cover surface	Rubber 3mm thick
Bottom surface	Carcass
Top surface hardness	55 $\pm$ 5 $^{\circ}$ shoreA
Elongation	1/2% Max.

Note: Party shall mention detailed specification like total length/width/thickness, thickness of top cover/ply, hardness, Max. Elongation, type of carcass, belting etc. of offered wear belt in their offer.

4. Read

Wear belt technical specifications			
Duty To work as vacuum seal belt for horizontal belt filter under 600mm Hg vacuum. Top surface will be sealing surface and bottom surface will slide on UHMWPE slide blocks. Plain water will be lubricant. For Horizontal belt filter size 4.2mtr x 110 m ²			
Description	Specifications	Tolerance	Unit
Fabric tension Layer	Polyester, 3 ply		
Top layer	PVC Cover		
Bottom side	Fabric- Low friction		
Hardness Top side	55-60		Shore A
Force at 1% Elongation	45 da		N/cm
Belt thickness	6	± 0.5	mm
Belt width	50	± 2	mm
Belt Length	56850	± 25	mm
Joint type	Endless (closed end) - Hot spliced		
Thickness of top cover	0.5	+ 0 / 0.2	mm
Temperature range	Ambient Max 45 deg. C		deg 'C'
Bending Radius	Minimum normal flexing dia 250 mm back fixing dia 350 mm		

(SK BARMAN)
DGM(Purchase)